

## CMA ACOUSTICAL SYSTEMS

SYSTEM	STANDARD THICKNESS	STANDARD DENSITY	STANDARD WIDTHS	MAX WIDTH	STANDARD LENGTH	MAXIMUM LENGTH	STANDARD FACINGS	ACOUSTICAL RANGE
Quiet Coordinates	2"	Dual 1.8 & 3#	48, 60"	60"	4, 5, 8, 10'	10'	Matte	.90 - 1.00
Encapsulated Pads & Rolls	1/2 - 6"	3/4 - 7#	12, 18, 24, 36, 48"	72"	2, 4'	10' - PVC 30' - Poly	Poly, PVC	.65 - 1.15
Baffle Systems	1, 1-1/2, 2"	1-1/2 - 7#	18, 24, 36, 48"	48"	2, 4'	10'	PVC, Matte, Sailcloth	.90 - 1.15
Wall Panel Systems	1 - 2"	2-1/2, 3, 4, 6#	24, 48"	48"	4, 8'	10'	PVC, Sailcloth, Glass	.65 - 1.15
Banner Systems	1 - 4"	1, 1-1/2, 2#	48"	48"	8'	30'	Sailcloth, Perf, PVC	.85 - 1.15
Absorption Plus	6"	3/4#	46"	46"	8'	12'	PVC, Sailcloth	1.45 - 1.55
Ceiling Panels	1 - 2"	3#	20, 24, 48, 60"	60"	4, 5, 8, 10'	10'	Glass Cloth 5 Patterns	.85 - 1.00
Hygienic Ceilings & Walls	1, 1-1/2, 2"	4#	24"	48"	2, 4'	5'	White Tedlar PVF	.85 - 1.00

**NOTES:** 1. Other facings, densities and thicknesses may be available as a custom product. 2. Acoustical performance will vary with thickness and type of facing, density and thickness of fiberglass base. 3. Maximum length will vary according to facing selected. 4. Other acoustical properties such as CAC (STC) are available: Call CMA, Inc. to discuss.